

Weatherproof HD IP Camera

Brand: ZEBRA

Model: Z-73

General Features

- Megapixel HD Network Waterproof IR Bullet Camera
- Omnivision\Aptina\SONY CMOS Sensor With TI DaVinci™ DSP
- H.264 Compression, Dual-stream Encoding, POE Optional
- 1080P@25fps\960P@25fps\720P@25fps
- Support ONVIF 2.0, NVR/CMS Recording
- Megapixel HD Lens 8mm
- 5X42PCS IR LED, IR Distance: 40M, With IR-CUT



Model NO.	Z-73-1.0M	Z-73-1.3M	Z-73-2.0M
Camera			
Image Sensor	1/4" OV9715 CMOS	1/3" ARO130 CMOS	1/2.8" SONY IMX222 CMOS
Main processor	Hi3518C	Hi3518C	Hi3516C
Resolution	720P	960P	1080P
Effective Pixels	1280(H)*720(V)	1280(H)*960(V)	1920(H)*1080(V)
TV System	PAL/NTSC		
Electronic Shutter Time	Auto: PAL 1/50-1/100, 000Sec; NTSC 1/60-1/100, 000Sec		
Sync System	Internal		
Usable Illumination	1Lux	0.1Lux	0.1Lux
S/N Ratio	≥52dB		
Scanning System	Progressive		
Video Output	Network		
Lens			
Focus Length	8mm		
Focus Control	Manual		
Lens Type	Manual		
Pixels	2M Pixels	2M Pixels	3M Pixels
Night Vision			
Infrared LED	5X42PCS		
Infrared Distance	40M		
IR Status	Under 10 Lux By CDS		
IR Power On	CDS Auto Control		
Network			
Ethernet	RJ-45 (10/100Base-T)		
Protocol	IPv4, HTTP, TCP/IP, FTP, NTP, RTSP, UDP, SMTP, DNS, DDNS		
ONVIF	Support ONVIF 2.0		
P2P	YES, Support		
POE	Optional		

WIFI	N/A		
Frame Rate	25fps(PAL)/30fps (NTSC) (1-25/1-30 FPS adjustable)		
Dual Stream	Main Stream: 1280*720 Sub Stream: 704*576, 352*288	Main Stream: 1280*960, 1280*720 Sub Stream: 704*576, 352*288	Main Stream: 1920*1080, 1280*720 Sub Stream: 704*576, 352*288
IE Brower	IE6-10		
Smart Phone	iPhone, iPad, Android		
Camera Features			
Day/Night	Color/ B&W		
Compression	H.264		
Picture config	Saturation/Brightness/Contrast /Sharpness		
Motion Detection	Support		
Privacy Masking	3 Rectangular Zone		
Recording Mode	NVR/Multi window/Web		
Language	English		
General			
Weatherproof Housing	YES, IP66		
Anti-cut Bracket	YES, Cable built-in Bracket		
IR Cut Filter	YES		
Operation Temperature	-10°C ~ +50°C RH95% Max		
Storage Temperature	-20°C ~ +60°C RH95% Max		
Power Source	DC12V±10%, 1000mA		
Dimension	275(W)x90.5(H)x79.5(D)mm		
Weight	1.4Kg		
Origin	Taiwan		

